

Administrative Stuff

You should have a tlab account by now; check your spam traps if you didn't get email about it.

Class is Mondays and Fridays now.

Reminder: sign up for the mailing list.

The Arbitrariness of Identifiers

The “Are the following two programs equivalent?” game

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)  (+ x 1))  
(f 10)
```

```
(define (f y)  (+ y 1))  
(f 10)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ x 1))  
(f 10)
```

```
(define (f y) (+ y 1))  
(f 10)
```

yes

argument is consistently renamed

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ x 1))  
(f 10)
```

```
(define (f x) (+ y 1))  
(f 10)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ x 1))  
(f 10)
```

```
(define (f x) (+ y 1))  
(f 10)
```

no

not a use of the argument anymore

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ x 1))  
(f 10)
```

```
(define (f y) (+ x 1))  
(f 10)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ x 1))  
(f 10)
```

```
(define (f y) (+ x 1))  
(f 10)
```

no

not a use of the argument anymore

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f z) (+ y 1))  
(f 10)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f z) (+ y 1))  
(f 10)
```

yes

argument never used, so almost any name is ok

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f y) (+ y 1))  
(f 10)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f y) (+ y 1))  
(f 10)
```

no

now a use of the argument

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f x) (+ z 1))  
(f 10)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x) (+ y 1))  
(f 10)
```

```
(define (f x) (+ z 1))  
(f 10)
```

no

still an undefined identifier, but a different one

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f z)
  (local [(define y 10)]
    (+ z y)))
(f 0)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f z)
  (local [(define y 10)]
    (+ z y)))
(f 0)
```

yes

argument is consistently renamed

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f x)
  (local [(define z 10)]
    (+ x z)))
(f 0)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f x)
  (local [(define z 10)]
    (+ x z)))
(f 0)
```

yes

local identifier is consistently renamed

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f x)
  (local [(define x 10)]
    (+ x x)))
(f 0)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f x)
  (local [(define x 10)]
    (+ x x)))
(f 0)
```

no

local identifier now hides the argument

The Arbitrariness of Identifiers

Are the following two programs equivalent?

```
(define (f x)
  (local [(define y 10)]
    (+ x y)))
(f 0)
```

```
(define (f y)
  (local [(define y 10)]
    (+ y y)))
(f 0)
```

The Arbitrariness of Identifiers

Are the following two programs equivalent?

(define (f x) (local [(define y 10)] (+ x y))) (f 0)	(define (f y) (local [(define y 10)] (+ y y))) (f 0)
---	---

no

local identifier now hides the argument

Free and Bound Identifiers

An identifier for the argument of a function or the name of a local identifier is a ***binding occurrence***

```
(define (f x y) (+ x y z))
```

```
(local [ (define a 3)
         (define c 4) ]
       (+ a b c))
```

Free and Bound Identifiers

A use of a function argument or a local identifier is a
bound occurrence

```
(define (f x y) (+ x y z))
```

```
(local [ (define a 3)
         (define c 4) ]
        (+ a b c))
```

Free and Bound Identifiers

A use of an identifier that is not function argument or a local identifier is a **free identifier**

```
(define (f x y) (+ x y z))
```

```
(local [ (define a 3)
         (define c 4) ]
       (+ a b c))
```

Arithmetic Language

```
<AE> ::= <num>
         |
         { + <AE> <AE> }
         |
         { - <AE> <AE> }
```

Arithmetic Language

```
<AE> ::= <num>
         |
         { + <AE> <AE> }
         |
         { - <AE> <AE> }
```

```
(define-type AE
  [num (n number?)]
  [add (lhs AE?)
        (rhs AE?)]
  [sub (lhs AE?)
        (rhs AE?)])
```

Arithmetic Language

```
<AE> ::= <num>
         | { + <AE> <AE> }
         | { - <AE> <AE> }
```

```
(define (interp an-ae)
  (type-case AE an-ae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))])
    [sub (l r) (- (interp l) (interp r))]))
```

Arithmetic Language

```
<AE> ::= <num>
         | { + <AE> <AE> }
         | { - <AE> <AE> }
```

```
(define (interp an-ae)
  (type-case AE an-ae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))])
    [sub (l r) (- (interp l) (interp r))]))
```

No identifiers to help us study binding...

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

With Arithmetic Language

```
<WAE> ::= <num>
          |
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

```
{with {x {+ 1 2}}
      {+ x x}}           ⇒   6
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

x \Rightarrow error: free identifier

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

```
{+ {with {x {+ 1 2}}
      {+ x x}}
{with {x {- 4 3}}
      {+ x x}} } }      ⇒     8
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

```
{+ {with {x {+ 1 2}}
      {+ x x}}
{with {y {- 4 3}}
      {+ y y}} } }           ⇒     8
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

```
{with {x {+ 1 2}}
  {with {x {- 4 3}}
    {+ x x}}}}      ⇒  2
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

```
{with {x {+ 1 2}}
  {with {y {- 4 3}}
    {+ x x}}}
                         ⇒   6
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>} NEW
          | <id> NEW
```

```
(define-type WAE
  [num (n number?)]
  [add (lhs WAE?)
        (rhs WAE?)]
  [sub (lhs WAE?)
        (rhs WAE?)]
  [with (name symbol?)
        (named-expr WAE?)
        (body WAE?)]
  [id (name symbol?)])
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r)) ]
    [sub (l r) (- (interp l) (interp r)) ]
    [with (bound-id named-expr body-expr)
      ...]
    [id (name) ...]))
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>} NEW
          | <id> NEW
```

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))])
    [sub (l r) (- (interp l) (interp r))])
    [with (bound-id named-expr body-expr)
      ...]
    [id (name) (error 'interp "free variable")]))
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW
```

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))])
    [sub (l r) (- (interp l) (interp r))])
    [with (bound-id named-expr body-expr)
      ... (interp named-expr) ...]
    [id (name) (error 'interp "free variable")]))
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>} NEW
          | <id> NEW
```

```
(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r))])
    [sub (l r) (- (interp l) (interp r))])
    [with (bound-id named-expr body-expr)
      ... (interp named-expr)
      ... (interp body-expr) ...])
    [id (name) (error 'interp "free variable")]))
```

With Arithmetic Language

```
<WAE> ::= <num>
          | {+ <WAE> <WAE>}
          | {- <WAE> <WAE>}
          | {with {<id> <WAE>} <WAE>}    NEW
          | <id>                                NEW

(define (interp a-wae)
  (type-case WAE a-wae
    [num (n) n]
    [add (l r) (+ (interp l) (interp r)) ]
    [sub (l r) (- (interp l) (interp r)) ]
    [with (bound-id named-expr body-expr)
      (interp (subst body-expr
                      bound-id
                      (interp named-expr))) ]
    [id (name) (error 'interp "free variable") ])))
```

Substitution

```
; subst : WAE symbol num -> WAE
(define (subst a-wae sub-id val)
  (type-case WAE a-wae
    [num (n) ...]
    [add (l r) ...]
    [sub (l r) ...]
    [with (bound-id named-expr body-expr)
          ...]
    [id (name) ...]))
```

Substitution

```
; subst : WAE symbol num -> WAE
(define (subst a-wae sub-id val)
  (type-case WAE a-wae
    [num (n) ...]
    [add (l r) ...]
    [sub (l r) ...]
    [with (bound-id named-expr body-expr)
          ...]
    [id (name) ...]))
```

Let's make examples/tests first...

Example Sustitutions

```
; 10 for x in {+ 1 x}
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))
;
; 10 for x in x
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))
;
; 10 for x in x ⇒ 10
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))
```

```
; 10 for x in x ⇒ 10
(test (subst (id 'x) 'x 10)
           (num 10))
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))

; 10 for x in x ⇒ 10
(test (subst (id 'x) 'x 10)
           (num 10))

; 10 for x in y
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))

; 10 for x in x ⇒ 10
(test (subst (id 'x) 'x 10)
           (num 10))

; 10 for x in y ⇒ y
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))
```

```
; 10 for x in x ⇒ 10
(test (subst (id 'x) 'x 10)
           (num 10))
```

```
; 10 for x in y ⇒ y
(test (subst (id 'y) 'x 10)
           (id 'y))
```

Example Sustitutions

```
; 10 for x in {+ 1 x} ⇒ {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))

; 10 for x in x ⇒ 10
(test (subst (id 'x) 'x 10)
           (num 10))

; 10 for x in y ⇒ y
(test (subst (id 'y) 'x 10)
           (id 'y))

; 10 for y in {- x 1}
```

Example Sustitutions

```
; 10 for x in {+ 1 x} => {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
            (add (num 1) (num 10)))  
  
; 10 for x in x => 10
(test (subst (id 'x) 'x 10)
            (num 10))  
  
; 10 for x in y => y
(test (subst (id 'y) 'x 10)
            (id 'y))  
  
; 10 for y in {- x 1} => {- x 1}
```

Example Sustitutions

```
; 10 for x in {+ 1 x} => {+ 1 10}
(test (subst (add (num 1) (id 'x)) 'x 10)
           (add (num 1) (num 10)))  
  
; 10 for x in x => 10
(test (subst (id 'x) 'x 10)
           (num 10))  
  
; 10 for x in y => y
(test (subst (id 'y) 'x 10)
           (id 'y))  
  
; 10 for y in {- x 1} => {- x 1}
(test (subst (sub (id 'x) (num 1)) 'y 10)
           (sub (id 'x) (num 1))))
```

Substitution

```
; subst : WAE symbol num -> WAE
(define (subst a-wae sub-id val)
  (type-case WAE a-wae
    [num (n) a-wae]
    [add (l r) (add (subst l sub-id val)
                      (subst r sub-id val))]
    [sub (l r) (sub (subst l sub-id val)
                      (subst r sub-id val))]
    [with (bound-id named-expr body-expr)
          ...]
    [id (name) (if (symbol=? name sub-id)
                  (num val)
                  a-wae))]))
```

Example Sustitutions

```
; 10 for x in {with {y 17} x}
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} ⇒ {with {y 17} 10}
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} => {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
            (with 'y (num 17) (num 10)))
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} => {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
            (with 'y (num 17) (num 10)))
;
; 10 for x in {with {y x} y}
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} => {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
            (with 'y (num 17) (num 10)))

; 10 for x in {with {y x} y} => {with {y 10} y}
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} => {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
            (with 'y (num 17) (num 10)))

; 10 for x in {with {y x} y} => {with {y 10} y}
(test (subst (with 'y (id 'x) (id 'y)) 'x 10)
            (with 'y (num 10) (id 'y)))
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} => {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
            (with 'y (num 17) (num 10)))

; 10 for x in {with {y x} y} => {with {y 10} y}
(test (subst (with 'y (id 'x) (id 'y)) 'x 10)
            (with 'y (num 10) (id 'y)))

; 10 for x in {with {x y} x}
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} => {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
            (with 'y (num 17) (num 10)))

; 10 for x in {with {y x} y} => {with {y 10} y}
(test (subst (with 'y (id 'x) (id 'y)) 'x 10)
            (with 'y (num 10) (id 'y)))

; 10 for x in {with {x y} x} => {with {x y} x}
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} => {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
            (with 'y (num 17) (num 10)))

; 10 for x in {with {y x} y} => {with {y 10} y}
(test (subst (with 'y (id 'x) (id 'y)) 'x 10)
            (with 'y (num 10) (id 'y)))

; 10 for x in {with {x y} x} => {with {x y} x}
(test (subst (with 'x (id 'y) (id 'x)) 'x 10)
            (with 'x (id 'y) (id 'x)))
```

Example Sustitutions

```
; 10 for x in {with {y 17} x} => {with {y 17} 10}
(test (subst (with 'y (num 17) (id 'x)) 'x 10)
            (with 'y (num 17) (num 10)))

; 10 for x in {with {y x} y} => {with {y 10} y}
(test (subst (with 'y (id 'x) (id 'y)) 'x 10)
            (with 'y (num 10) (id 'y)))

; 10 for x in {with {x y} x} => {with {x y} x}
(test (subst (with 'x (id 'y) (id 'x)) 'x 10)
            (with 'x (id 'y) (id 'x)))
```

Substitution

Substitution replaces

- free identifiers with the same name
- no binding identifiers
- no bound identifiers

Substitution

Substitution replaces

- free identifiers with the same name
- no binding identifiers
- no bound identifiers

An identifier is bound when it appears in the body of a **with** binding the same name

Conversely, a free variable of a name appears in a **with** only if the **with** doesn't bind the name

Substitution

```
; subst : WAE symbol num -> WAE
(define (subst a-wae sub-id val)
  (type-case WAE a-wae
    ...
    [with (bound-id named-expr body-expr)
      (with bound-id
        (subst named-expr sub-id val)
        (if (symbol=? bound-id sub-id)
            body-expr
            (subst body-expr sub-id val))))]
    ...))
```

HW 2

Implement

```
; free-ids : WAE -> list-of-sym  
;  
; binding-ids : WAE -> list-of-sym  
;  
; bound-ids : WAE -> list-of-sym
```